

[illegible]

Police sidrati v abel temelje min. 25 cm globoko z injekcijsko maso HILTI-HIT HY 200

10.226

3.58

25

50

50

100

3.68

D

C

The technical drawing shows a vertical section of a reinforced concrete column. The main reinforcement consists of four longitudinal bars labeled ①ø8/20, spaced at 20 mm from each other and 25 mm from the edges. There are also three sets of cross-ties labeled ③¼ø10 and ③ø10. A horizontal dimension line indicates a total width of 65 mm. Vertical dimensions show distances of -3.58, -3.98, and -4.48 from a reference level. Other dimensions include 40, 50, and 10.

Technical drawing of a cross-section of a concrete structure, likely a bridge pier or abutment, showing reinforcement details and dimensions.

Reinforcement Details:

- ① 23 ϕ 8/20 (Longitudinal bars in the lower section)
- ② 23 ϕ 10/20 (Longitudinal bars in the upper section)
- ③ 4 ϕ 10 (Transverse bars in the upper section)
- ④ 4 ϕ 16 (Transverse bars in the upper section)
- ⑤ 4 ϕ 16 (Transverse bars in the upper section)

Dimensions and Levels:

- Overall width: 445
- Overall height: 274
- Top level: -3.98
- Intermediate level: -4.48
- Bottom level: -7.22
- Section width at top: 50
- Section width at bottom: 65

Labels:


- pusti beton (Concrete casting)

The diagram illustrates the cross-section of a reinforced concrete slab with various reinforcement components labeled as follows:

- 1** Ø 226: Main longitudinal reinforcement bar.
- 2** Ø 8 / 20: Secondary longitudinal reinforcement bars.
- 3** ± 4 Ø 10: Additional longitudinal reinforcement bars.
- 4** Ø 8 / 20: Torsional reinforcement bars.
- 5** Ø 16: Top reinforcement bar near the column face.
- 6** 4 Ø 16: Bottom reinforcement bars near the column face.

Dimensions and specifications include:

- Vertical dimensions from the top surface: -3.58 m, -3.98 m, and -4.48 m.
- Horizontal dimensions at the bottom: 25 cm, 14 cm, 50 cm, 50 cm, and 45 cm.
- Reinforcement specification: "Palice sidrati v obst. temelje min. 25 cm globoko z injekcijsko maso HILTI-HIT HY 200".
- Column labels: D and C.

 TECTUM d.o.o. PROJEKTIRANJE GRADBENIH KONSTRUKCIJ SLO – 2000 MARIBOR, Mladinska ul. 5 e-mail: gorazd.debeljak@tectum.si tel.: +386 2 22 80 040	
Investitor: UKC MARIBOR Ljubljanska ulica 5 2000 Maribor	Odgovorni vodja projekta: Marko SORŠAK univ.dipl.inž.arh. Identifikacijska številka: ZAPS 0567 A
Objekt: PRIZIDEK IZGRADNJA DVEH DIAGNOSTIČNIH TERAPEVTSKIH PROSTOROV	Odgovorni projektant: Gorazd DEBELJAK , univ.dipl.inž.grad. Identifikacijska številka: IZS G – 1730
Vrsta načrta: NAČRT GRADBENIH KONSTRUKCIJ	Projektanti/sodelavci:
Vrsta projekta: P Z I	Številka projekta: 11–10/2014
Vsebina risbe: TEMELJI NEPODKLETENEGA DELA ARMATURNI NAČRT	Številka načrta: 15/2014 Datum: januar 2015 Merilo: 1:50 Štev. risbe: PZI 03